

L500 Semi-Automatic L-Sealing Systems

Models: L500SA (as pictured with TM 18 shrink tunnel) and L800SA.



The L500SA and L800SA L-Sealers can be used to pack your products in a safe and presentable way. Easy adjustment/settings of these sealers guarantees flexibility a high production quantities. These sealers can also be used in combination with our separate shrink tunnels.

System	L500SA	L800SA
Seal dimensions	560 x 430 mm	870 x 620 mm
Max. product height	230 mm	300 mm
Max. film reel	600 mm	800 mm
Max. film reel diameter	300 mm	300 mm
Film thickness	10-50 micron	
Film	PVC, Polyolefin, Polyethylene micro perforated	
Production capacity	600-1200 pph*	500 – 900 pph*
Power supply	230V +/- 10% 1Ph – 50/60 Hz	
Power consumption	2500W	3100W
Machine size (LxWxH)	2020 x 790 x 1055 mm	3015 x 1005 x 1125 mm
Shipping size (LxWxH)	1400 x 880 x 1190 mm	2130 x 1080 x 1300 mm
Machine weight	148 Kg (gross 180 Kg)	247 Kg (gross 300 Kg)

* The production speed depends on the product size and material used.

Product features:

- Semi-automatic L-sealer.
- Automatic cycle mode.
- Scrap film winder.
- Scrap film guide device.
- Teflon-coated sealing blade.
- Liquid cooling circuit.
- Control glass for cooling liquid level.
- Working height sealer and tunnel adjustable.
- Emergency button.
- Automatic transfer of the product to the shrink tunnel.
- Adjustable shrink delay time for sealing thin films.

- User-friendly control panel with LCD allowing:
 - *Machine information.*
 - *Counter.*
 - *Sealing temperature settings.*
 - *Conveyor speed.*
 - *Automatic cycle mode setting.*
 - *6 operating programs.*
 - *Failure codes indication.*

Options	L500 SA	L800 SA
Support for double reel	Option	Not available
Film waste winding device	Standard included	